

ADJUSTABLE SUPPORT PADS (ASP – TD Range)

| Material | Wallbarn Support Pads are manufactured from high quality virgin polypropylene and allows indoor and outdoor laying in normal atmospheric conditions with all technical-physical and mechanical properties maintained in the longterm. Manufacture of all support pads conform to quality management systems standard UNI EN ISO 9001:2008. |
|----------------|--|
| Application | Wallbarn Support Pads can be laid on all secure and stable floor surfaces allowing inspection under slabs or decking without demolition. Installation in external areas helps protect the waterproof surface and allows practical use of the terrace. |
| Technical data | The polypropylene support pads can be laid with temperatures from -40°C to 75°C. The material is particularly resistant to sudden temperature changes, resists acid, alkaline and atmospheric agents. |

| | Physical-Mechanical Properties | | | | | | | | | | | |
|---|--------------------------------|-----------------------|--------------------------------|----------------------------------|---------------------------------|--|--|--|--|--|--|--|
| | Melt Flow Rate | Weight Density | VICAT with a load of 5kg | HDT with a load of 1820kPa | Coefficient of Elasticity | Impact Izod with engrading (IZOD at 23°C) | Impact Izod with engrading (IZOD at -20°C) | | | | | |
| Test Method | ASTM D1238 | ASTM D792 Method A | ASTM D1525 | ASTM D648 | ASTM D790 | ASTM D256 | ASTM D256 | | | | | |
| Unit | Gr/10 | Gr/cm ³ | °C | °C | Мра | J/m | J/m | | | | | |
| | 14-16 | 0.99-1.04 | >75 | >90 | >1600 | >40 | >20 | | | | | |
| Fire Rating | | | | | | | | | | | | |
| Wallbarn Adjustable Support Pads have been classed as 'EUROCLASSE E' according to EN 13501-1:2009 | | | | | | | | | | | | |

| Technical Data WALLBARN ADJUSTABLE SUPPORTS – FOR PAVING and TIMBER DECKING | | | | | | | | | | | |
|---|-------|-------|-------|--------|-----------|-------|-----|--|--|--|--|
| | | | | | | | | | | | |
| 25mm fixed | 120mm | 208mm | 2.2mm | 18.5mm | 40 & 60mm | 400kg | No | | | | |
| 35mm fixed | 120mm | 200mm | 2.2mm | 18.5mm | 40 & 60mm | 400kg | Yes | | | | |
| 35-50mm | 120mm | 208mm | 2.2mm | 18.5mm | 40 & 60mm | 400kg | No | | | | |
| 50-70mm | 120mm | 208mm | 2.2mm | 18.5mm | 40 & 60mm | 400kg | Yes | | | | |
| 65-100mm | 120mm | 208mm | 2.2mm | 18.5mm | 40 & 60mm | 400kg | Yes | | | | |
| 95-130mm | 120mm | 208mm | 2.2mm | 18.5mm | 40 & 60mm | 400kg | Yes | | | | |
| 125-160mm | 120mm | 208mm | 2.2mm | 18.5mm | 40 & 60mm | 400kg | Yes | | | | |
| 155-190mm | 120mm | 208mm | 2.2mm | 18.5mm | 40 & 60mm | 400kg | Yes | | | | |
| 185-220mm | 120mm | 208mm | 2.2mm | 18.5mm | 40 & 60mm | 400kg | Yes | | | | |

Wallbarn Ltd. Tandridge Priory, Barrow Green Road, Oxted, Surrey RH8 9NE Tel: + 44 (0) 1883 715983 Fax: + 44 (0) 1883 623670 Email: sales@wallbarn.com Web: www.wallbarn.com